# Continental

### Refrigerator

## 60" FRONT BREATHER SANDWICH UNIT REFRIGERATORS



#### **Standard Features**

- Unique Air Flow Distribution Allows Pan Product to Maintain 33°–41°F Being in Compliance with and Certified Under the '98 NSF Standard For Preparation Units.
- · Modern, State-of-the-Art Styling
- Performance Rated Refrigeration System Utilizing Environmentally Safe R-134a Refrigerant
- Easily Serviceable Back Mounted Compressor
- 2" Non-CFC Polyurethane Foam Insulation
- · Spring Loaded, Self Closing Door
- Magnetic Snap-In Gasket
- 35/8" Casters, two with brakes, two without brakes
- · Heavy-Duty, Epoxy-Coated Steel Shelves
- · Interior Hanging Thermometer
- · Full Length Nylon Cutting Board
- Cabinet Construction Consisting of Stainless Steel Front and Top, Aluminum End Panels, Case Back and Interior
- · Non-Corrosive, Plasticized Fin Evaporator Coil
- · Completely Enclosed, Vented and Removable Case Back
- Automatic, Energy Saving, Non-Electric Condensate Disposal
- 1/4 Size Pans, 4" Deep
- · 10 ft Cord and Plug Attached

#### **Models Available**

- SW60-8-FB
- SW60-8C-FB
- SW60-12M-FB

- SW60-12-FB
- SW60-12C-FB
- SW60-18M-FB

- SW60-16-FB
- SW60-16C-FB
- SW60-24M-FB

Utilizing Environmentally Safe, CFC-free R-134a Refrigerant



#### **Optional Features & Accessories**

- Electric Condensate
- Pan Opening Sizes
- Stainless Steel End Panels-SA Models
- Stainless Steel Interior & Exterior-SS Models
- Stainless Steel Finished Back in Lieu of Aluminum
- · Remote Models R
- Additional Shelves
- Door Locks
- · Single Overshelf
- · Double Overself
- Drawers

#### **60" FRONT BREATHER SANDWICH UNIT REFRIGERATORS**

SPECIFICATIONS SW	/ -60-8-FB	-60-12-FB	-60-16-FB	-60-8C-FB	-60-12C-FB	-60-16C-FB	-60-12M-FB	-60-18M-FB	-60-24M-FB
DIMENSIONAL DATA									
Net Capacity (cu. ft.)	17.0	17.0	17.0	17.0	17.0	17.0	17.0	17.0	17.0
<sup>1</sup> / <sub>6</sub> Size Pans	8	12	16	8	12	16	12	18	24
Width, Overall (in.)	60	60	60	60	60	60	60	60	60
Depth, (incl. Hdls.& Bumpers) (in.)	31	31	31	31	31	31	31	31	31
Depth, Body Only (Less Door(s)(in.)	$27^{1}/_{2}$	$27^{1}/_{2}$	$27^{1}/_{2}$	$27^{1}/_{2}$	$27^{1}/_{2}$	$27^{1}/_{2}$	$27^{1}/_{2}$	$27^{1}/_{2}$	$27^{1}/_{2}$
Depth, Cutting Board	12	12	12	19	19	19	10	10	10
Height, Overall (incl. 35/8" Casters) (in.)		40 7/8	40 7/8	40 7/8	40 7/8	40 7/8	40 7/8	40 7/8	40 <sup>7</sup> / <sub>8</sub>
Shelf Area (sq. ft.)	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1
No. of Shelves	2	2	2	2	2	2	2	2	2
No. of Doors	2	2	2	2	2	2	2	2	2
Condensing Unit Size (H.P.)	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4
Refrigerant	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R-134a	R-134a
Cabinet Electrical	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1
Amps	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.2
Fans	3	3	3	3	3	3	3	3	3
Interior Depth (in.)	20	20	20	20	20	20	20	20	20
Interior Height (in.)	26 <sup>1</sup> / <sub>4</sub>	26 <sup>1</sup> / <sub>4</sub>	26 <sup>1</sup> / <sub>4</sub>	26 <sup>1</sup> / <sub>4</sub>	26 <sup>1</sup> / <sub>4</sub>	26 <sup>1</sup> / <sub>4</sub>	26 <sup>1</sup> / <sub>4</sub>	26 <sup>1</sup> / <sub>4</sub>	26 <sup>1</sup> / <sub>4</sub>
Interior Width (in.)	56	56	56	56	56	56	56	56	56
Shipping Weight (lbs.)	309	311	315	315	315	315	319	322	330
Shipping Height (in.)	431/4	431/4	431/4	431/4	431/4	431/4	431/4	431/4	431/4
Shipping Length (in.)	68 <sup>1</sup> / <sub>4</sub>	68 <sup>1</sup> / <sub>4</sub>	68 <sup>1</sup> / <sub>4</sub>	68 <sup>1</sup> / <sub>4</sub>	68 <sup>1</sup> / <sub>4</sub>	68 <sup>1</sup> / <sub>4</sub>	68 <sup>1</sup> / <sub>4</sub>	68 <sup>1</sup> / <sub>4</sub>	68 <sup>1</sup> / <sub>4</sub>
Shipping Depth (in.)	46	46	46	46	46	46	46	46	46
227/8									
60"					-	— 60 — <del>-</del>		60 —	
30° 313/4 34 34 34 34 34 34 34 34 34 34 34 34 34									19 • 19
					3 1/4		3 1/4		
34 31/4 SW60-12C	SW60-160	31 3/4 — 10 — 10 — 10 — 10 — 10 — 10 — 10 — 1	34	60	0 10	34	60 ————————————————————————————————————	0 10	

